

# BradyPrinter i3300 & BBP33 Label Printer comparison



[www.bradyeurope.com/i3300](http://www.bradyeurope.com/i3300)

Brady's no-waste, 20-second changeover printer is getting even better. In addition to a new look and name, there are several functional enhancements in the new BradyPrinter i3300 from its predecessor the BBP33 Printer.

Specifications	BBP33 Label Printer	BradyPrinter i3300
<b>Touch screen</b>	No	Yes, in <b>full colour</b> , with faster and easier interface experience to change settings
<b>Display content</b>	Ribbon and label part number installed, amount of supplies remaining, receiving printing data, ready state/error state	Ribbon and label part number installed, <b>one-touch material size and colour details</b> , amount of supplies remaining, <b>Wi-Fi connection</b> , receiving printing data, ready state/error state
<b>Compatible media</b>	B30 or B33 series media roll cartridges, B30-R series one-color ribbon cartridges	B30 or B33 series media roll cartridges, B30-R series one-color ribbon cartridges
<b>Top applications</b>	Product identification, wire identification, circuit board identification, lab identification, safety and facility identification	Product identification, wire identification, circuit board identification, lab identification, safety and facility identification, <b>floor marking</b>
<b>Auto cutter</b>	Built-in, steel blade	Built-in, <b>non-stick coated to cut ToughStripe material</b> , redesigned for <b>better access for cleaning</b>
<b>Sensors</b>	1 gap sensor, 1 side notch sensor, 1 center notch sensor	1 gap sensor, 1 side notch sensor, 1 center notch sensor, <b>dust shields added for enhanced print registration and more effective cleaning</b>
<b>Max. print speed</b>	Up to 101.6 mm/sec	Up to 101.6 mm/sec
<b>Processor 32 bit clock rate</b>	32 bit 312 MHz clock rate	<b>32 bit 800 MHz clock rate</b> (more efficient and powerful)
<b>Memory</b>	64 MB (RAM) - 4 GB (data storage)	<b>512 MB (RAM) - 195 MB (data storage)</b>
<b>Connectivity options</b>	1 x USB, 1 x Ethernet 10/100 BASE-T, 1 x USB 2.0 for PC connection	<b>2 x USB</b> , 1x Ethernet 100 BASE-T, <b>WiFi</b> , 1 x USB 2.0 for PC connection
<b>Networking</b>	Replaceable Brady Network card with Ethernet 10/100 BASE-T	<b>Network module integrated on main board with Ethernet 100 BASE-T and more reliable network connection</b>
<b>Software compatibility</b>	LabelMark, Brady Workstation, Windows based driver for 3rd party software use, direct-to printer scripting (BPL)	Brady Workstation, Windows based driver for 3rd party software use, direct-to printer scripting (BPL)
<b>Fan</b>	Always runs	<b>Can be turned off, filter pads added, helps reduce dust accumulation inside printer</b>
<b>Size</b>	W 231 x H 241 x D 305	W 231 x H 241 x D 305
<b>Weight (kg)</b>	5	5
<b>Warranty</b>	1 year	1 year